

Vivitek D803W-3D

WXGA projector with built-in 2D to 3D content conversion technology



Product Features

- Bright 3500 lumens and a crisp 3000:1 contrast ratio for a perfect image
- Integrated 2D to 3D content conversion technology
 - Automatically converts almost any 2D content into 3D ready material for enhanced viewing pleasure
- WXGA native resolution for wide image display
- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Connectivity options including: HDMI V1.3, VGA-In, Composite Video, Audio-In and RS-232C
- 3D ready for amazing visuals
- Built-in 10W audio speaker
- Security solutions include: Kensington® security slot, security bar, keypad lock
- Great portability at 3.6kg

Product Photos



| Product Specifications | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display Type | DLP |
| Brightness | 3600 Lumens |
| Native Resolution | WXGA (1280 x 800) |
| Maximum Resolution | UXGA (1600 x 1200) |
| Contrast Ratio | 3000 :1 |
| Lamp Life and Type | 3,000/4000 Hours (Std./Eco. Mode), 240W |
| Throw Ratio | 1.536 - 1.712:1 |
| Image Size (Diagonal) | 27" @1m~302" @10m |
| Projection Distance | 1.2 - 10m (3.94ft to 32.8ft) |
| Projection Lens | F = 2.52 - 2.72, f = 21.35 - 24.49mm |
| Zoom Ratio | 1.1x |
| Aspect Ratio | 16:10 Native, 4:3, 16:9 Compatible |
| Offset | 123% |
| Keystone Correction | Vertical +/- 40° |
| Horizontal Frequency | 15, 31-102KHz |
| Vertical Scan Rate | 48 - 120Hz |
| Speakers | 10W (Mono) |
| Lens Shift Range | N/A |
| Video Compatibility | SDTV (480i, 576i), EDTV (480p), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM |
| I/O Connection Ports | HDMI 1.3V (x2), VGA-In, S-Video, Component, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), Audio-Out (Mini-Jack), RS-232C, USB (Service) |
| Projection Method | Table Top, Ceiling Mount (Front or Rear) |
| Security Solutions | Kensington® Security Slot, Security Bar, Keypad Lock |
| Dimensions (W x D x H) | 285 x 261 x 130 mm |
| Weight | 2.7Kg (6 lbs) |
| Noise Level | 34dB/31dB (Std. / Eco. Mode) |
| Power Supply | AC 100-240V, 50/60Hz |
| Power Consumption | 240W (Eco. Mode), 280W (Std. Mode), <0.5W (Standby) |
| Standard Accessories | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit |
| Optional Accessories | Replacement Lamp, Remote, Carrying Case |

©2012 Vivitek Corporation. Vivitek is a trademark of Vivitek Corporation. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

